


XVS-16 / 17

SCHLAUCHVERSCHRAUBUNG

- ✓ Schlauchverschraubung mit zylindrischem Whitworth-Rohrgewinde
- ✓ Nach DIN / ISO 228



Artikel	PN	Gewinde	Schlauch (ID)	Schlauch (AD)	Material
XVS-161803	LL	G 1/8"	3 mm	5 mm	VA-Stahl
XVS-161804	LL	G 1/8"	4 mm	6 mm	VA-Stahl
XVS-161806	LL	G 1/8"	6 mm	8 mm	VA-Stahl
XVS-161808	LL	G 1/8"	8 mm	10 mm	VA-Stahl
XVS-161404	LL	G 1/2"	4 mm	6 mm	VA-Stahl
XVS-161406	LL	G 1/4"	6 mm	8 mm	VA-Stahl
XVS-161408	LL	G 1/4"	8 mm	10 mm	VA-Stahl
XVS-161410	LL	G 1/4"	10 mm	12 mm	VA-Stahl
XVS-163804	LL	G 3/8"	4 mm	6 mm	VA-Stahl
XVS-163806	LL	G 3/8"	6 mm	8 mm	VA-Stahl
XVS-163808	LL	G 3/8"	8 mm	10 mm	VA-Stahl
XVS-163810	LL	G 3/8"	10 mm	12 mm	VA-Stahl
XVS-161208	LL	G 1/2"	8 mm	10 mm	VA-Stahl
XVS-161210	LL	G 1/2"	10 mm	12 mm	VA-Stahl
XVS-171406	L	G 1/4"	6 mm	8 mm	VA-Stahl
XVS-171408	L	G 1/4"	8 mm	10 mm	VA-Stahl
XVS-173806	L	G 3/8"	6 mm	8 mm	VA-Stahl
XVS-173806	L	G 3/8"	8 mm	10 mm	VA-Stahl
XVS-173810	L	G 3/8"	10 mm	12 mm	VA-Stahl